

AD-A068 427

WASHINGTON STATE UNIV PULLMAN SHOCK DYNAMICS LAB
SHOCK-INDUCED DECOMPOSITION OF CARBON DISULFIDE.(U)
APR 79 G E DUVAL
WSU-SDL-79-02

F/G 7/2

N00014-77-C-0232
NL

UNCLASSIFIED

1 OF 1
ADA
068427



END
DATE
FILMED

6 79
DDC


LEVEL

12
B.S.

SHOCK-INDUCED DECOMPOSITION OF CARBON DISULFIDE

George E. Duval

Department of Physics
Washington State University
Pullman, WA 99164



Annual Summary Report
for the period
4/1/78 - 3/31/79

Research Sponsored by the Office of Naval Research, Contract No.
N00014-77-C-0232; NR 092-558.

Reproduction in whole or in part is permitted for any purpose of
the United States Government.

Approved for public release: distribution unlimited.

April 1979

79 05 07 114

AD A068427

DDC FILE COPY

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER WSU SDL 79-02	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) 6 Shock-Induced Decomposition of Carbon Disulfide.		5. TYPE OF REPORT & PERIOD COVERED 4/1/78- Annual Summary 3/31/79
7. AUTHOR(s) 10 George E. Duval		6. PERFORMING ORG. REPORT NUMBER 14 WSU-SDL-79-02
9. PERFORMING ORGANIZATION NAME AND ADDRESS Physics Department Washington State University Pullman, WA 99164		8. CONTRACT OR GRANT NUMBER(s) 15 N00014-77-C-0232
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research 800 N. Quincy St. Arlington, VA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 092-558
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Resident Rep. University District Bldg., Room 422 1107 NE 45th Street Seattle, WA 98195		12. REPORT DATE 11 Apr 1979
16. DISTRIBUTION STATEMENT (of this Report) 9 Annual summary rept. 1 Apr 78 - 31 Mar 79 Approved for public release; distribution unlimited.		13. NUMBER OF PAGES 17
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
18. SUPPLEMENTARY NOTES		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Shock Waves Carbon Disulfide Decomposition Chemistry		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The purpose of this work is to study the shock-induced chemical decomposition of liquid CS ₂ . Studies of mechanical response have shown that the liquid under compression transforms to a higher density form. Past work has shown that this transformation occurs under static pressure at 45 kb and 175°C. Previous shock experiments have shown that a similar transformation occurs in a single shock at approximately 60 kb and 1000°C. Sheffield at WSU has shown that the transformation occurs in a reflected shock at pressures		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

403 690

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. (continued)

greater than 75 kb and at temperatures greater than 750°C. The transformation or reaction time was determined by Sheffield in various ways and found to decrease from about 400 nsec at 79 kb to less than 10 nsec at 130 kb. At the lower pressures there is an induction time decreasing from 300 nsec at 79 kb to less than 6 nsec at 106 kb.

In the year just completed attention has turned from mechanical to optical aspects of the reaction. A major effort has gone into repair, installation and calibration of the time-resolving spectrograph to be used for absorption spectroscopy. Similar effort has been expended on measurement of light emitted from the CS₂ when shocked. This work has produced new information on radiation from shocked PMMA, but it hasn't yet been determined whether or not the CS₂ emits characteristic radiation when shocked. Finally, a significant effort was devoted to study and evaluation of shock tube experiments on the kinetics of CS₂ decomposition. It's concluded that the results have little bearing on expectations for shocked liquid CS₂.

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY NOTES	
PL	SP. CIAL
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

SUMMARY

The purpose of this work is to study the shock-induced chemical decomposition of liquid CS_2 . Studies of mechanical response have shown that the liquid under compression transforms to a higher density form. Past work has shown that this transformation occurs under static pressure at 45 kb and 175°C. Previous shock experiments have shown that a similar transformation occurs in a single shock at approximately 60 kb and 1000°C. Sheffield at WSU has shown that the transformation occurs in a reflected shock at pressures greater than 75 kb and at temperatures greater than 750°C. The transformation or reaction time was determined by Sheffield in various ways and found to decrease from about 400 nsec at 79 kb to less than 10 nsec at 130 kb. At the lower pressures there is an induction time decreasing from 300 nsec at 79 kb to less than 6 nsec at 106 kb.

In the year just completed attention has turned from mechanical to optical aspects of the reaction. A major effort has gone into repair, installation and calibration of the time-resolving spectrograph to be used for absorption spectroscopy. Similar effort has been expended on measurement of light emitted from the CS_2 when shocked. This work has produced new information on radiation from shocked PMMA, but it hasn't yet been determined whether or not the CS_2 emits characteristic radiation when shocked. Finally, a significant effort was devoted to study and evaluation of shock tube experiments on the kinetics of CS_2 decomposition. It's concluded that the results have little bearing on expectations for shocked liquid CS_2 .

I. PROBLEM STATEMENT

In a 1977 paper, Yakusheva, Yakushev and Dremin reviewed work on the transparency and shock compression of several carbon-bearing materials.¹ They proposed that there is sufficient justification to suppose that loss of transparency under shock and existence of a cusp in the Hugoniot P-V curve are correlated. They noted that in such cases the carbon bonds are unsaturated and proposed that either transparency loss or a cusp in the Hugoniot is evidence of pressure-induced pyrolysis of unsaturated carbon compounds, leading to the formation of free carbon.

Sheffield, here at Washington State University, had undertaken a study of mechanical parameters of CS₂ under shock conditions, having postulated that a cusp in the Hugoniot at 60 kb reported by R. Dick² corresponds to chemical decomposition of the compound. His work has set in motion a continuing effort to investigate as thoroughly as possible the physical, chemical and optical events associated with this shock-induced transition of liquid CS₂ to a higher density state.

Carbon disulphide is a colorless liquid at room temperature and atmospheric pressure. It has a density of 1.26 g/cc and heat of formation from graphite and solid sulfur of 22 kcal/mol, indicating that it is metastable under these conditions. P. W. Bridgman, in 1942, reported that, under hydrostatic pressures greater than 45 kb and temperature of 175°C or more, there is a "slow and irreversible change to a black solid, permanent under atmospheric conditions - a new form of CS₂."³ The density of this new substance he reported to be 4% greater than an aliquot mixture of carbon and sulfur.

Later work by Whalley,⁴ Butcher, Alsop, Weston, and Gebbie,⁵ and Chan and Jouscher⁶ indicated that this new material is composed of two different substances, and that it decomposes to carbon and sulfur at 170°C and atmospheric pressure with an energy of release of 16 kcal/mol.



Afanasenkov and associates calculated a Hugoniot curve for a mixture of carbon and sulfur and found that it agreed with measurements by R. Dick at high pressures. They also measured the brightness temperature of CS_2 shocked to the high density state and found it to be approximately 500°C higher than their calculated values. From both these results they inferred the existence of a shock-induced decomposition with release of heat.⁷

Sheffield, in a procedure inverse to that of Afanasenkov et al., inferred an equation of state for the decomposition products from R. Dick's Hugoniot data at high pressures.⁸ His best fit corresponds to a density at room temperature which is in close agreement with the density of a statically compressed mixture of carbon and sulfur. The equation of state of the products, combined with a similar equation of state of CS_2 shows the latter to be metastable or unstable throughout the entire range of pressures and temperatures accessible by shock.

The kinetics of CS_2 decomposition in the vapor phase has been studied using shock tube and optical spectroscopy techniques. The two principal works are by Gaydon and colleagues, who measured absorption spectra,⁹ and Arnold and colleagues, who measured emitted light.^{10,11} In the former work, absorption was measured for CS_2 , CS and S_2 . The latter two appeared as the former disappeared, and the results were compatible with the assumption that reaction was occurring according to



Arnold et al. measured light emission throughout the visible spectrum. They felt their results to be incompatible with Eq. (1) and proposed



They also found an induction time preceding the reaction for temperatures below

2600°K, whereas Gaydon et al. found no evidence of induction. Both groups of workers agreed that the reaction was second-order in CS₂ concentration, with reaction constants

$$k_2 = 10^{14.2} e^{-43.7\text{kcal/RT}}, \quad \text{Gaydon et al.}$$

$$k_2 = 10^{11.53} e^{-45.2\text{kcal/RT}}, \quad \text{Arnold et al.}$$

In experiments where CS₂ vapor has been excited by electron impact or UV light, it appears to be common to observe spectra of CS and $\dot{\text{S}}$ but not S₂. This is peculiar because the heat of formation of S₂ relative to S under standard conditions is about -34 kcal/mol.

The problems faced in the WSU program have been to, first, determine what parameters which will yield significant chemical information for liquid CS₂ can best be measured in a shock environment where pressures may exceed 100 kb for only one or two microseconds before the assembly is destroyed, and, second, to devise an experimental design which will allow the measurements to be made.

At the time this research was started, we had on loan from the U.S. Air Force a vacuum spectrograph coupled with a rotating mirror streak camera which is capable of providing a record of the evolution in time of the spectrum of any light source presented, limited in wavelength only by the quartz lens in the streak camera and the sensitivity of film. This instrument had not been operated since it had arrived on campus, nor for a number of years before that. It was evident that if it could be made to operate, it could provide exactly the kind of information we require to unravel the chemical kinetics. We therefore set about designing an experiment which would be compatible with the requirements for absorption spectroscopy, and which would also provide the "global parameters" of the experiment. That is, the regimes of pressure and temperature for which the rate of reaction was in a range suitable for study with time resolution in the range 20 to 50 nsec.

This initial phase of the research, carried out by S. A. Sheffield, was completed in the spring of 1978. The major results are described in the Annual Summary Report for this contract, 4/1/77 to 3/31/78. They are briefly summarized here.

Design of the experiment is illustrated in Fig. 1. A high impedance impactor moving at high speed is allowed to strike the plane face of a PMMA cell filled with CS_2 . The shock induced in the PMMA is shown as state "0" in Fig. 1c. This shock passes through the PMMA and transmits the shock state labeled "1" into the CS_2 . The CS_2 shock travels through the cell at a pressure below that required to produce decomposition and reflects from the sapphire back plate of the cell on reflection; the shock state "3'" is produced in the unreacted CS_2 , and this decays to state "3" as reaction proceeds. As the reflected shock travels back through the cell, it breaks into two waves: a precursor in CS_2 corresponding to some state "2" and the reaction shock carrying the material to state "3" in the reaction products.

By introducing EM velocity gages at various positions in the cell, Sheffield was able to

- 1) detect the decay from 3' to 3;
- 2) trace the development of the three-wave structure;
- 3) record the risetime of the reaction shock in the reflected wave.

In addition to this, he recorded an unexpected, quasi-coherent electrical noise which appears to be associated with the reaction and decays approximately as the reaction decays.

In items 1, 2, and 3 above all give information about reaction rate. Characteristic reaction times vary from less than 10 nsec when state 3' is greater than 100 kb to several hundred nanoseconds for $3' \approx 80$ kb. Temperatures in the unreacted CS_2 range from about 1000 to 1200°K. At the lower pressures there is clear indication of an induction time preceding the reaction. It ranges in magnitude up to 300 nsec.

At the completion of this phase of the work Dr. Sheffield went to the Sandia





Fig. 1 Experimental Sketch and Shock Diagrams for the CS₂ Experiments. (a) shows the experimental layout, i.e. a sapphire impactor hitting a CS₂ cell with a PMMA front and a sapphire back. (b) shows the direction of the shocks produced and the various states achieved.




Fig. 1 (continued). (c) shows the states achieved in pressure-particle velocity space. Notice the relaxation that takes place from state 3' to state 3 as the reaction proceeds.

Laboratories in Albuquerque, and our attention at WSU turned to the problems of spectroscopy.

II. THE TIME-RESOLVING SPECTROGRAPH

This instrument was manufactured by Beckman and Whitley in San Carlos, CA (since absorbed by the Cordin Co.). It consists of the Model 339B Continuous Writing Streak Camera coupled with a Model 1500 Spectrographic Dispersion Unit. Except for a single quartz lens in the camera, all optical components are reflectors. It can be evacuated, and with the proper grating it can operate from deep in the ultraviolet well into the infrared.

Physically the instrument is a monster, being about 6 ft by 4-1/2 ft by 3 ft overall, weighing about 1500 lbs. It was necessary to have the turbine for the camera mirror rebuilt, and this was done by the Cordin Co. The original grating was ruled at 150 lines/mm, which is suitable for the visible and infrared, and this has been replaced by a 600 lines/mm grating with peak efficiency at about 3000 Å. Internal reflectors had become coated with oil, and it was necessary to disassemble the instrument and clean all reflecting surfaces.

The instrument has been installed on a platform above the gun in which the projectile is accelerated. It is situated so that it looks vertically downward into the target chamber. In operation, light from a flash lamp will be allowed to pass through the sapphire back plate of the CS₂ cell, through a thin layer of CS₂ bounded by the sapphire and a reflecting foil in a plane parallel to the back face of the sapphire. After reflecting from the foil it will again traverse the thin layer of CS₂ in which absorption is occurring and be conveyed to entrance slit of the spectrograph. The primary limit on time resolution is provided by thickness of the layer between sapphire and reflector. For a layer 0.1 mm thick and a reflected shock velocity of 4 mm/μsec, the time required for the shock to traverse the layer is

.025 μ sec, and the absorption measurement will be averaged over this time interval. This is probably about the best that can be achieved. Whether or not it is possible to do this well remains to be determined.

The limiting time resolution of the camera is 5 nsec. The time resolution which can be realized depends on spectral resolution, light intensity, and film sensitivity. Limiting spectral resolution with the 600 lines/mm grating is about 2 \AA . In our initial experiments, no such resolution is required. With a blackbody light source at 6000°K and spectral resolution of 64 \AA , an exposure of 28 nsec puts $.05 \text{ ergs/cm}^2$ on the film, which is enough to insure adequate exposure with no extraordinary measures taken to sensitize the film. Our presently available source is a Xe flash lamp which corresponds approximately to a blackbody at 6000 degrees. It is adequate for preliminary purposes, but if reflection and absorption losses in the cell are severe, it may be submarginal. In that case, or if greater spectral resolution is required, it will be necessary to provide a higher temperature source. Some work has been done toward this end.

Calibration of the camera-spectrograph has turned out to be a major task. It is approaching an end, and we expect to begin preliminary absorption experiments soon.

III. SHOCK-STIMULATED RADIATION

There have been some reports of light emitted from shocked solids and liquids.¹² It has been largely from experiments in which shock pressure was several hundred or more kilobars. In most cases it has been identified as blackbody radiation. In a few experiments non-equilibrium radiation has been reported.

Five experiments have been performed looking for light emission associated with the onset of reaction when the initial shock reflects from the sapphire back plate. The results are interesting because unexpected. They haven't yet provided much information about CS_2 . They are listed in the following table.

Light Emission Experiments

<u>No.</u>	<u>Cell</u>	<u>Spectral Region</u>	<u>Results</u>
1	Standard, CS ₂ filled	visible	light
2	Standard, CS ₂ filled	blue and red	light
3	CS ₂ replaced by PMMA	blue and red	light
4	Solid cell of black PMMA	blue and red	light
5	Brass cell filled with CS ₂	blue and red	no blue

The experiments involved photomultiplier tubes set up to look through the sapphire back plate along the cell axis. In the first experiment a single PM tube was used; in the others there were two tubes: one with a blue lo-pass filter and one with a red hi-pass filter. Optics were glass so the total spectral range was little more than the visible.

In all experiments but the last there was a great deal of light. In each case the record of PM output vs time could be closely correlated with shock events in the cell. In the first experiment there was an intense flash at the instant of impact, presumed due to compression of residual gas between impactor and target. This was followed by a period of decaying intensity and a second, weaker flash when the first shock reflected from the sapphire back face. Following this, the intensity increased with time as if optical depth were large and the increase in shocked volume produced a corresponding increase in observed light. Then this, too, was quenched at about the time the rarefaction from the back of the sapphire impactor reached the reflected shock. This event was followed by a long, intense light which might reasonably have been associated with the breakup of the cell. The close time correlation of the various events with intensity was encouraging and we elected to do a second CS₂ experiment.

In the second CS₂ experiment blue and red filters were added to separate thermal radiation (which peaks in the infrared) and any characteristic radiation in the blue

or near ultraviolet. The impact surface was shielded to eliminate radiation from compressed gases. In this experiment, too, there was a great deal of light, but red and blue outputs were uncorrelated, and neither correlated properly with shock events. Something had gone wrong with the timing. It was evident, however, that there were a lot of light sources other than the shocked CS_2 , so we decided to do a control experiment with PMMA replacing the CS_2 . In this third experiment there was also a lot of light in both blue and red. Records from the two PM tubes were well-correlated and were time-correlated with shock events. Light increased sharply when the first shock reflected from sapphire, and thereafter followed a course similar to that of the first CS_2 cell, but with greater intensity. PMMA is obviously unsuitable cell material for a light emission experiment.

Experiment no. 4 was a second control experiment with the cell made entirely of black PMMA. It produced even more light than the clear PMMA.

The cell in experiment no. 5 was constructed of brass and the optics were arranged so the PM tubes looked through a window in the side of the cell. This arrangement has the disadvantage that the field of view includes a non-uniform shocked region and a curved shock front. A low intensity burst of red light was recorded at the time the first shock entered the CS_2 , and it was followed by increasing light intensity until the shock reached the brass face at the back of the cell. At that moment the intensity decreased instead of increasing, and the later light output did not correlate well with shock events. It is not clear what happened. The observations may have been affected by

1. Microscopic bubbles of entrapped gas at the brass- CS_2 interface where first light was recorded.
2. Refraction of light by curved shock front may have diverted light from the field of view of the optical system and effectively obscured the source after the first short interval.
3. The decrease in intensity may be real and may indicate that the reaction is endothermic, not exothermic.

Further speculation at this point is fruitless. Another experiment is in progress which has the same geometry as the first four. The cell will be of brass, except for a sapphire back plate. There is some concern about the effect of fluorescence from the sapphire, but it will not fluoresce unless excited, and if it is excited, it will be because UV radiation from the CS_2 exists, unless shock excitation alone produces light.[^] So in our crude division of the spectrum we will still be able to distinguish between red and blue and measure the influence of various events on the emitted light.

IV. EXAMINATION OF SHOCK TUBE EXPERIMENTS

With the assistance of Henry Chung, who was briefly a post-doctoral student on this contract, the analysis in Reference 11 has been carefully examined for any light it may shed on reactions to be expected in liquid CS_2 . The result has been to generate some skepticism about the validity of such experiments. There appear to be at least two questionable assumptions normally made in this type of experiment; both are implicit:

1. In the state immediately behind the shock front the gas is in thermal equilibrium and has not yet started to react.
2. The state of flow behind the shock is that of the permanent regime, i.e., each physical variable, f , depends on position, x , and time, t , in such a way that $f = f(x - U_s t)$.

The first assumption is questionable because of the different relative rates at which translational, rotational and vibrational degrees of freedom come to equilibrium. The second may or may not be sound, but there is no evidence in references 9-11 that the question has been considered.

In browsing through proceedings of the 1970 Shock Tube Symposium,¹³ I see some evidence of a developing awareness of these problems at that time. An interesting fact reported by Nicholls and Pritchard is that dissociation of polyatomic molecules is first order at high pressures and second order at low pressures. The work on CS_2

reported in references 9-11 was carried out at low pressures - a few mm of Hg; and the authors in both cases agreed that the decomposition in liquid CS_2 at high pressure should be first order, but that is not strictly in accord with Sheffield's results. Some further consideration of this problem appears to be in order.

What appears to be a common error in the use of shock tubes to study gas phase kinetics turned up in the process of evaluating reference 11. It appears to be common practice to write the kinetic equation for a first-order reaction in the form

$$\frac{dn}{dt} = -k_1 n \quad (4)$$

where n is number of mols per unit volume of the species considered. A first-order reaction, as I understand it, is analogous to the decay of nuclear species. A molecule just sits around waiting for something internal to happen. When it does, it decomposes or reacts. The presence or absence of adjacent molecules has no effect on the reaction. In that case, Eq. (3) is improper in a system of changing density. Consider N molecules in a volume V which is changing with time. The first order reaction as I have defined it is described by the equation

$$\frac{dN}{dt} = -k_1 N \quad (5)$$

It is perfectly proper to divide both sides of Eq. (5) by V , but the result is

$$\frac{1}{V} \frac{dN}{dt} = -k_1 n, \quad (6)$$

not Eq. (4). Eq. (6) can also be written

$$\frac{dn}{dt} = -(k_1 - \frac{d \ln p}{dt}) n \quad (7)$$

where p is mass per unit volume and V has been assumed to be the volume of unit mass. It is evident that if the rate of density change is of the same order as rate of

reaction, the difference between Eqs. (4) and (7) can be very significant. Whether it is in fact so for a particular experiment would require detailed examination of that experiment.

V. FUTURE PLANS

Very careful planning will be required if the absorption experiment is to succeed. A lot of time will be devoted to that and to getting the apparatus ready for the measurement.

A decision will be made soon as to whether or not the work on light emission will be pursued further. If characteristic radiation exists, it will be worthwhile. If not, the work to date will be published in a note for the benefit of other experimenters.

A great deal of time will be devoted to the questions of interpretation of spectra and the study of kinetic processes in CS_2 .

REFERENCES

1. O. B. Yakusheva, V. V. Yakushev, and A. N. Dremine, "Relation Between Loss of Transparency by Carbon Compounds under High Dynamic Pressure and Anomalies on the Impact Compressibility Curves," Russian J. Phys. Chem. 51, 973 (1977).
2. R. Dick, J. Chem. Phys. 52, 6021 (1970).
3. P. W. Bridgman, Collected Experimental Papers (Harvard, Cambridge, 1964), Vol. VI, p. 413.
4. E. Whalley, Can. J. Chem. 38, 2105 (1960).
5. E. G. Butcher, M. Alsop, J. A. Weston, and H. A. Gebbie, Nature 199, 756 (1963).
6. W. S. Chan and A. K. Jouscher, Phys. Status Solidi 32, 749 (1969).
7. A. N. Afanasenkov, I. M. Voskoboinikov, M. F. Gogulya, and A. I. Karkov, Fiz. Goreviya i Vzryva 10, 583 (1974).
8. S. A. Sheffield, "Shock-Induced Reaction in Carbon Disulfide," (Ph.D. Thesis, Washington State University, 1978); S. A. Sheffield and G. E. Duvall, "Shock-Induced Decomposition of Carbon Disulfide," presented at the H. D. P. Symposium, Paris, France, 1978. Proceedings to be published.
9. A. G. Gaydon, G. H. Kimbell and H. B. Palmer, Proc. Roy. Soc. A279, 313 (1964).
10. S. J. Arnold and G. H. Kimbell, J. Phys. Chem. 73, 3751 (1969).
11. S. J. Arnold, W. B. Brownlee, and G. H. Kimbell, J. Phys. Chem. 74, 8 (1970).
12. An extensive review was published by S. B. Kormer in Soviet Physics Uspekhi, 11, No. 2, 229-254 (1964). More recent work is by P. A. Urtiew and R. Grover, J. Appl. Phys. 45, No. 1, 140-145 and 146-152 (1974). The radiation from CS₂ in Ref. 7 was for 165 kb and 3000°K.
13. I. I. Glass, ed., Shock Tubes (U. Toronto, 1970). See especially "Spectroscopic and Kinetic Studies in Shock Tubes" by R. W. Nicholls and H. O. Pritchard, and "Shock Tube Diagnostics, Instrumentation and Fundamental Data" by R. I. Soloukhin.

DISTRIBUTION LIST

Office of Naval Research
Code 473
Arlington, VA 22217
Attn: Dr. R. Miller

Office of Naval Research
1030 East Green Street
Pasadena, CA 91106
Attn: Dr. R. Marcus

Office of Naval Research
495 Summer Street
Boston, MA 02210
Attn: Dr. L.H. Peebles

Office of Naval Research
536 S. Clark Street
Chicago, IL 60605
Attn: Dr. J. Smith

Defense Documentation Center
Bldg. 5
Cameron Station
Alexandria, VA 22314

Office of Naval Research Res. R.
University of Washington
3710 Brooklyn Ave. NE. Unit #2
Seattle, WA 98195

U.S. Naval Research Lab.
Code 2627
Washington, DC 20375

U.S. Naval Research Lab.
Code 2629
Washington, DC 20375

Naval Weapons Center
Research Department
Code 60
China Lake, CA 93555

Naval Air Systems Command
Code 440
Washington, DC 20360
Attn: Dr. H. Rosenwasser

Naval Sea Systems Command
SEA-0331
Washington, DC 20362
Attn: Mr. J. Murrin

Naval Sea Systems Command
SEA-0332
Washington, DC 20362
Attn: Dr. M. Stosz

Naval Surface Weapons Center
Research and Tech. Dept.-WR
Silver Spring, MD 20910

Naval Weapons Center
Attn: Ronald L. Derr
Code 608
China Lake, DA 93555

Air Force Office of Sci. Res.
Directorate of Aerospace Sci.
Bolling Air Force Base
Washington, DC 20332

U.S. Army Research Office
Chemistry Division
P.O. Box 12211
Research Triangle Park, NC 27709

AFRPL (MKP)
Edwards, CA 93523
Attn: Mr. R. Geisler

Naval Research Lab.
Code 6100
Washington, DC 20375

John Hopkins Univ. APL
Chemical Propulsion Info. Agen.
John Hopkins Road
Laurel, MD 20810
Attn: T. W. Christian

Naval Surface Weapons Center
Code 240
Silver Spring MD 20910
Attn: S. J. Jacobs

Princeton University
Forrestal Campus Library
P.O. Box 710
Princeton, NJ 08540

Technical Director, Proj. Squi
Purdue University
Lafayette, IN 47907
Attn: Prof. S.N.B. Murthy

Army Ballistic Research Lab.
Aberdeen Proving Grounds, MD 21005
Attn: A.W. Barrows/DRDAR-BLP

U.S. Army Research Office
Physics Division
P.O. Box 12211
Research Triangle Park, NC 27709

Air Force Office of Sci. Res.
Directorate of Chemical Sci.
Bolling Air Force Base
Washington, DC 20332

Air Force Office of Sci. Res.
Directorate of Physics
Bolling Air Force Base
Washington, DC 20332

Commander
Naval Weapons Center
China Lake, CA 93555
Attn: D. Lind

Hercules Incorporated
Allegany Ballistics Laboratory
P.O. Box 210
Cumberland, MD 21502
Attn: Library

Commanding Officer
Picatinny Arsenal
Dover, NJ 07801

J. Hershokowitz
Picatinny Arsenal
Dover, NJ 07801

SARPA-TS-S #59
Picatinny Arsenal
Dover, NJ 07801

M. Finger
Lawrence Livermore Lab.
University of CA
P.O. Box 808
Livermore, CA 94550

E. James
Lawrence Livermore Lab.
University of CA
P.O. Box 808
Livermore, CA 94550

E. Lee
Lawrence Livermore Lab.
University of CA
P.O. Box 808
Livermore, CA 94550

J. Kury
Lawrence Livermore Lab.
University of CA
P.O. Box 808
Livermore, CA 94550

D. Hayes
Sandia Laboratories
P.O. Box 5800
Albuquerque, NM 87185

Director
Los Alamos Scientific Lab.
P.O. Box 1663
Los Alamos, NM 87545

Library
Los Alamos Scientific Lab.
P.O. Box 1663
Los Alamos, NM 87545

L. C. Smith
Los Alamos Scientific Lab.
P.O. Box 1663
Los Alamos, NM 87545

B. G. Craig
Los Alamos Scientific Lab.
P.O. Box 1663
Los Alamos, NM 87545

A. Popolato
Los Alamos Scientific Lab.
P.O. Box 1663
Los Alamos, NM 87545

Dr. L. Zernow
Shock Hyrdodynamics, Inc.
15010 Ventura Bl.
Sherman Oaks, CA 91403

D. Curran
Stanford Research Institute
333 Ravenswood Ave.
Menlo Park, CA 94025

M. Cowperthwaite
Stanford Research Institute
333 Ravenswood Ave.
Menlo Park, CA 94025

Rohm and Haas
Huntsville Defence Contract
723-A Arcadia Circle
Huntsville, AL 35801

H. M. Schuey
Huntsville Defense Contract
723-A Arcadia Circle
Huntsville, AL 35801